

LED Receiving Card

UNV-A5S-PLUS



Specifications

Model	UNV-A5S-PLUS
Maximum Resolution	
Maximum Resolution	<p>PWM driver IC</p> <ul style="list-style-type: none"> – 512 × 384@60 Hz (8 bit video sources) – 256 × 384@60 Hz (10 bit and 12 bit video sources) <p>Common driver IC</p> <ul style="list-style-type: none"> – 384 × 384@60 Hz (8 bit video sources) – 192 × 384@60 Hz (10 bit and 12 bit video sources)
General	
Input voltage	DC 3.8 V to 5.5 V
Rated current	0.6 A
Rated power consumption	3.0 W

Product Dimensions (W × H × D) (mm)	70.0 × 45.0 × 8.3
Net weight (g)	16.2 Note: It is the weight of a single receiving card only.
Operating Temperature	-20°C to 70°C
Operating Humidity	10% RH to 90% RH, non-condensing
Storage Temperature	-25°C to 125°C
Storage Humidity	0% RH to 95% RH, non-condensing

Ordering Info

Product Model	Description
UNV-A5S-PLUS	LED Receiving Card

Zhejiang Uniview Technologies Co., Ltd.

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China (Zhejiang) Pilot Free Trade Zone, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

<http://www.uniview.com>

©2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

*Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.