

24" IT Monitor

MW-LC24



Features


- Resolution is up to at 1920 x 1080.
- Refresh rate up to 75Hz.
- 178° horizontal and vertical viewing angle.
- Screen can reduce blue light, protect eyes.
- Plastic body, ultra-narrow bezel, light weight and elegant.
- Shielding cover design, effectively preventing electromagnetic radiation.
- Stable structure design, highly durable.
- Automatically detect if the signal is connected successful.
- Support multiple language.

Specifications


Model	MW-LC24
Panel	
Backlight	LED
Panel Size	24"
Pixel Pitch (H x V) (mm)	0.27 x 0.27
Resolution	1920 × 1080
Color Support	16.7 M
Brightness (cd/m ²)	250
Contrast Ratio	3000:1
Refresh Rate	75 Hz
Response Time (ms)	14
Viewing Angle (H/V)	Horizontal 178°, Vertical 178°
Operation Hour	18/7
Bezel Width	2.55mm (top/left/right) 20.57mm (bottom)
Color Gamut	72% NTSC
Surface Treatment	Haze 25%, 3H
LCD Technology/Panel Type	VA
Interface	
Video Input	1 x HDMI, 1 x VGA
VESA	
VESA (mm)	100 x 100
Wall-mounted Thread	4-M4 Threaded Hole
OSD	
Multi-Language	16 (English, French, Spanish, Portuguese, German, Italian, Dutch, Swedish, Finnish, Polish, Czech, Russian, Korean, Chinese Simplified, Chinese Traditional, Japanese)
General	
Input Voltage	DC 12 V, 2 A
Typical Power Consumption (W)	≤24 (On)
Standby Power Consumption (W)	≤0.5 (Standby)

Package Dimensions (W x H x D) (mm)	601 x 400 x 145
Weight (Kg)	Net Weight: 3.4 Gross Weight: 4.4
Operating Temperature	0°C ~ 50°C
Operating Humidity	10% ~ 90% (No Condensation)
Storage Temperature	-10°C ~ 50°C
Storage Humidity	10% ~ 90% (No Condensation)
Standard	1 x HDMI Cable, 1 x Quick Guide, 1 x Pedestal, 1 x Adapter
Material	Plastic
Lifetime (h)	30000
Certifications	CE/FCC
MTBF	30000 h

Dimensions



Interface



Ordering Info

Product Model	Description
MW-LC24	24" IT Monitor

Zhejiang Uniview Technologies Co., Ltd.

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China (Zhejiang) Pilot Free Trade Zone, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

<http://www.uniview.com>

©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

*Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.