

75" Smart Interactive Display

MW3575-U-CA



Features

- 4K UHD anti-glare display delivers images with extreme detail.
- Ultra-narrow bezel design for perfect aesthetics.
- Dual Wi-Fi modules with both Wi-Fi and hotspot support.
- High-precision infrared touch technology allows up to 32-point touch, realizing smooth co-authoring.
- Multiple utility buttons on the front such as power, volume control, settings, etc.
- A variety of quick tools, such as annotation, screenshot, etc., with a floating window, improving usability and interaction efficiency.
- Wireless screen mirroring from various operating systems such as Android, iOS, and Windows to the display with one touch.
- Fast file transfer allows users to quickly transfer files from a mobile phone to the display via a QR code.
- OTA remote upgrade. The system can be upgraded online without backing up data.
- Split-screen writing. The whiteboard allows independent writing on two split screens at the same time.
- A variety of front interfaces allow users to easily and quickly plug/unplug USB drives and other tools.
- OCR recognition. The whiteboard can automatically recognize text and graphics.


Specifications


| Panel | Description |
|---------------------------------|--|
| Backlight | DLED backlight |
| Panel Size | 75" |
| Resolution | 3840 x 2160 |
| Brightness (cd/m ²) | 350 |
| Contrast Ratio | 1200 : 1 |
| Response Time (ms) | 8 |
| Viewing Angle (H/V) | 178°/178° |
| Color Support | 1.07 billion colors |
| Refresh rate (Hz) | 60 |
| Color gamut | 72% |
| Haze Value | 25% |
| Display Size (mm) | 1649.6 x 927.9 |
| Surface Hardness | 9H (7 on the Mohs scale) |
| Pixel Pitch (H x V) (mm) | 0.4296 x 0.4296 |
| Lifespan | 50000H |
| Touch | Description |
| Touch Control | Contactless IR sensor, supports 32-point touch, 20-point write |
| Touch Precision (mm) | ± 1 |
| Recognizable Object | 5 points, 3mm |
| Glass | 4mm tempered glass, level 7 on Mohs hardness scale, anti-glare |
| Touch Response Time (ms) | ≤ 5 |
| Touchscreen Input | Opaque objects (e.g. fingers, pens) |
| Touch technology | Infrared touch |
| System | Description |
| CPU | Amlogic T982 4 x A55 |
| CPU Frequency | 1.9 GHz |
| RAM/ROM | DDR4 : 4GB eMMC: 32GB |
| System Compatibility | Android 13.0 |

| Interface | Description |
|-----------------------|---|
| Video Input | 3 x HDMI IN (4K), 1 x VGA IN, 1 x AV IN, 1 x YPbPr IN, 1 x DP IN |
| Video Output | 1 x AV OUT, 1 x HDMI OUT (4K) |
| Audio Input | 1 x MIC_IN |
| Audio Output | 1 x EARPHONE, 1 x coaxial audio output interface (COAX) |
| Other Interfaces | 1 x RS232, 3 x front USB 3.0, 1 x on-board USB 2.0, 1 x on-board USB 3.0, 2 x TOUCH USB, 1 x Type-C, 1 x TF CARD |
| Network | 1 x LAN OUT, 1 x LAN IN |
| Audio | Description |
| Speaker | Left channel : 1 x treble (5 W) + 1 x bass (15 W) Right channel : 1 x treble (5 W) + 1 x bass (15 W) |
| Wi-Fi | Description |
| Wi-Fi Configuration | Wi-Fi 5+Wi-Fi 6, supports 5G/2.4G |
| Wi-Fi Performance | 30m ² coverage, 20m transmission distance in open space |
| Bluetooth | Description |
| Bluetooth Version | 5.2 |
| Bluetooth Performance | 10m transmission distance in open space |
| OSD | Description |
| Multi-Language | 23 (Simplified Chinese, Traditional Chinese, Japanese, German, English, Spanish, French, Italian, Portuguese, Russian, Korean, Vietnamese, Ukrainian, Hungarian, Polish, Thai, Arabic, Kazakh, Bulgarian, Galician, Catalan, Uzbek, Indonesian) |
| VESA | Description |
| Wall Mount Hole (mm) | 600 x 400 |
| Wall Mount Screw | 4-M8 screw hole |
| Camera | Description |
| Camera Resolution | Windows: Pixel 13MP for Photos & 13 MP for Video Android: Pixel 13MP for Photos & 1080P for Video |
| FOV | 118°/94°/75° |
| Microphone | Description |
| Microphone | 8 array microphone |
| Pickup Distance (m) | 8 m |
| General | Description |


| | |
|--|--|
| Power Supply | AC 100 to 240 V, 50/60 Hz |
| Overall Power Consumption (W) | 291.5 (without OPS) |
| Standby Power Consumption (W) | <0.5 |
| Product Dimensions (W x H x D) (mm) | 1720 x 1050 x 90 |
| Package Dimensions (W x H x D) (mm) | 1860 x 1173 x 212 |
| Operating Temperature | 0°C to 50°C |
| Weight (Kg) | Net weight: 53.0 Gross weight: 60.5 |
| Operating Humidity | 10% to 90% RH, non-condensing |
| Storage Temperature | -20°C to 60°C |
| Storage Humidity | 0% to 95% RH, non-condensing |
| Accessories Included | 1 x power cable, 2 x touch pen, 1 x quick guide, 1 x IR remote controller, 1 x wall mounting bracket |
| Certification | Description |
| Certification | Energy Star, CE LVD, CB, ERP, CE EMC, FCC, RCM |

Dimensions





Interface



Ordering Information for Optional Accessories

| Model | Remarks |
|-------------|---|
| MW3575-U-CA | 75" Smart Interactive Display |
| HB-7199-TP | Wireless Screen Sharing Dongle |
| HB-4365 | 65" to 86" smart interactive display wall mount bracket |
| HB-T-FMC | 65 to 86-Inch Smart Interactive Display Mobile Stand |
| HB-7099-M | Pluggable OPS PC module with i5 processor (Windows 10, not activated) |

| | |
|-------------|---|
| HB-7099-S | Pluggable OPS PC module with i7 processor (Windows 10, not activated) |
| LIS-WIN10-V | OS-Windows 10-1-to-1 License-IoT Enterprise Value (with i5 processor OPS module) |
| LIS-WIN10-H | OS-Windows 10-1-to-1 License-IoT Enterprise High End (with i7 processor OPS module) |

Ordering Info

| Product Model | Description |
|---------------|-------------------------------|
| MW3575-U-CA | 75" Smart Interactive Display |

Zhejiang Uniview Technologies Co., Ltd.

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

<http://www.uniview.com>

©2024 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

*Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.