

55" 0.88mm Bezel Width Video Wall



MW-A55-B5-E




Features

- Industrial-grade panel, highly reliable integrated structure design, continuous stable operation.
- Direct-lit LED backlight provides high brightness uniformity without border shadows.
- Ultra-narrow 0.88 mm seam.
- Supports white balance adjustment, delivering delicate and colorful images.
- Wide 178 viewing angles.
- Built-in image splicing function.
- Support anti-burn technology, landscape and portrait installation.
- Supports delayed boot after power on.
- Advanced direct-lit local dimming technology with low power consumption, saving energy.
- Metal case protects the unit from interference of radiation, magnetic fields, and strong electric fields.
- Support remote control and RS232 hoop control.
- Equipped with HDMI input Interfaces and HDMI loop out Interface, support video signal loop out display.
- Up to 4K@60Hz signal input by DP IN or HDMI interface, up to 4K@60Hz signal output by HDMI OUT interface.
- Compliant with HDCP2.3, HDCP2.2 and HDCP1.4.

Dimensions



Interface



Ordering Info

Product Model	Description
MW-A55-B5-E	55" 0.88mm Bezel Width Video Wall

Zhejiang Uniview Technologies Co., Ltd.

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

<http://www.uniview.com>

©2024 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

*Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.