

P2.5 Indoor Fine Pixel LED Display

MW7825-FI-ES



Features


- Advanced grayscale gives detailed and realistic images.
- Seamlessly splices images without black lines on the screen.
- Simple and stylish appearance, easy to install.
- High brightness and contrast provide optimal images.
- Takes up less space with a slim and compact design.
- Long lifetime.
- Low heat, excellent heat dissipation, no noise.
- Low failure rate and maintenance cost.
- Ultra-wide viewing angle ensures satisfactory viewing experience from diversified angles.
- High refresh rate and frame frequency provide high image quality without ghosting or smearing.
- Front maintenance.
- Power supply with a wide input voltage range, strong adaptability.
- Supports wall mount without reserving space for maintenance.
- Optional dual power supplies and dual receiving cards.


Specifications

Model	MW7825-FI-ES
Module	
Pixel Pitch	P2.5
Module Resolution (W × H)	120 x 67
Module Dimensions (mm)	300 x 168.75
Cabinet	

Modules Component (W × H)	2 x 2
Cabinet Dimensions (W × H × D) (mm)	600 x 337.5 x 32.3
Cabinet Resolution (W × H)	240 x 134
Material	Die-cast aluminum
Processing Image	
Single Pixel Brightness Correction	Support
Single Pixel Color Correction	Support
Brightness (nits)	600
Color Temperature (K)	6500 to 9300 adjustable
Viewing Angle (H/V)	160°/140°
Center Distance Deviation of LED	<3%
Brightness Uniformity	≥97%
Color Uniformity (Cx, Cy)	±0.003
Contrast Ratio	4000:1
Processing performance	
Pixel Density (pitch/m ²)	160000
Surface Evenness (mm)	≤0.2
Grayscale (bit)	14bit
Scanning Mode (S)	40
Drive Mode	Constant current driving
Refresh Rate (Hz)	≥3840
Electrical	
Power Supply	AC 100 to 240 V, 50/60 Hz
Average Power Consumption (W)	151
Max. Power Consumption (W/m ²)	455
General	
Maintenance Mode	Front maintenance
Ingress Protection	IP30
Weight (kg/pcs)	4.5
Operating Temperature	-10°C to +40°C
Operating Humidity	10% to 80% RH, non-condensing
Storage Temperature	-20°C to +60°C
Storage Humidity	10% to 85% RH, non-condensing
LED Lifetime (h)	50000

Dimensions





Ordering Info

Product Model	Description
MW7825-FI-ES	P2.5 Indoor Fine Pixel LED Display

Zhejiang Uniview Technologies Co., Ltd.

 <http://www.uniview.com>

 overseasbusiness@uniview.com; globalsupport@uniview.com

 No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China (Zhejiang) Pilot Free Trade Zone, China



©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

*Despite our best efforts, technical or typographical errors may exist in this document.

Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.